
WIZPANEL





INFRARED high speed operation



UHD 4K @ 60Hz Display



Screen Share good quality transmission



TUV anti-blue light approved



Dual OS easier to use



Anti Glare more comfortable view

Product Specifications

PHYSICAL SPECIFICAT	IONS		
 Model no	ILD-65H	ILD-75H	
Dispaly Size	65"	75"	
Active Area (mm)	1428.48x803.52 (64.53")	1650.24x928.26 (74.52")	
Display Ratio	16:9	16:9	
Brightness	370 cd/m2	370 cd/m2	
Physical Dimension	1507.2x932.6x89 mm	1729.4x1057.6x89.2 mm	
Packing Size	1646x1074x240 mm	1873x1204x240 mm	
NW	42kgs	55kgs	
GW	55kgs	71kgs	
DISPLAY		INTERACTIVITY	
Resolution	4K UHD (3840 x 2160 @ 60 Hz)	Touch Technology	Ultra Precise Inf
Display Colors	10 Bit + FRC (1.07 Billion)	Continuous Touch Points	Up to
Response Time	8 ms	Console Buttons	Power, Source, Menu,
Panel Refresh Rate	60 Hz	Touch Resolution	32768
LED Lifespan	50,000 hours	Response Time	≤
LCD Viewing Angle	178°	Touch Accuracy	1
Contrast Ratio	4000:01:00	Tracking Rate	6
Ambient Light Sensord	Yes	Scan Rate	20
Glass Hardness	9H (Pencil), 7 (Mohs)	Gestures and Edge Swipes	Windows
Glass Type	3mm Heat-tempered, Anti-Glare	Pen Type	Batter
CONNECTIVITY		Pen Tip Diameter	3
HDMI® 2.0 In(Front)	1	Palm Detection	
USB 2.0 (Front)	2	Annotation Over Any Source	
USB TOUCH (Front)	1	: CAMERA AND MIC	
Wi-Fi® (Rear)	1	Color bit	2
RJ45(Rear)	1	4K Resolution	3840x216
HDMI® 2.0 (Rear)	1	Image format	YUV
VGA In (Rear)	1	Viewing angle	Fixed-
Audio In (Rear)	1	MIC QTY	
RS232 (Rear)	1	Sampling res.	16
SD Card (Rear)	1	Sampling rate	16KH
YPbPr (Rear)	1	AEC Algorithm sampling rate	
HeadPhone Out (Rear)	1	COMPUTING	
AV In (Rear)	1	Operating System	Andr
AV Out (Rear)	1	RAM	5
SPDIF Out (Rear)	1	Internal Storage	1
USB 2.0 (Rear)	1	CPU	Quad Core: 2:
USB TOUCH (Rear)	1	CI O	2 x ARM
USB 3.0 (Rear)	Yes		
Wireless, 2x2	Included	AUDIO	
Bluetooth® 4.2	Included	Dual Front Facing Speakers	2 x 2
OPS Slot INSTALLATION	1	Audio Stereo ENVIRONMENTAL	Balance, Auto Volume
		Operating Temperature	0°C to 40°C
		120 120 120 120 120 120 120 120 120 120	

The installation of this product should be completed by a qualified installer. Use of components not supplied by Kozoni or not meeting minimum specifications may impact performance, safety and warranty. For more information please contact your local reseller or distributor.

WARRANTY

Warranty term and upgrade options vary by region. Contact your local reseller or distributor for information

370 cd/m2	400 cd/m2
1729.4x1057.6x89.2 mm	1975.6x1196.3x89.2 mm
1873x1204x240 mm	2120x1353x240 mm
55kgs	71kgs
71kgs	94kgs
	J-1Kg3
INTERACTIVITY	
Touch Technology	Ultra Precise Infrared Touch Sensor
Continuous Touch Points	Up to 20 Points
Console Buttons	Power, Source, Menu, VOL,CH, PC,Enter, Home
Touch Resolution	32768 x 32768 px
Response Time	≤ 5 ms
Touch Accuracy	1 mm
Tracking Rate	6 m/s
Scan Rate	200 Hz
Gestures and Edge Swipes	Windows® Supported
Pen Type	Battery-less Pen
Pen Tip Diameter	3 mm
Palm Detection	Yes
Annotation Over Any Source	Yes
CAMERA AND MIC	1 63
1 1 5	24 54
Color bit	24 bit
4K Resolution	3840x2160 /Opt. 20fps
Image format	YUV2, MJPG
Viewing angle	Fixed-focus 94°
MIC QTY	4
Sampling res.	16/24 bit
Sampling rate	16KHz - 48KHz
AEC Algorithm sampling rate	4 GB
COMPUTING	
Operating System	Android™ 8.0
RAM	2 GB
Internal Storage	16 GB
CPU	Quad Core: 2 x ARM Cortex A73,
	2 x ARM Cortex A53
AUDIO	
Dual Front Facing Speakers	2 x 20 Watts
Audio Stereo ENVIRONMENTAL	Balance, Auto Volume Control, Surround Sound
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-15°C to 55°C (-5°F to 131°F)
Operating Humidity	20% to 80% non-condensing humidity
Storage Humidity	20% to 90% non-condensing humidity
PACKED CONTENTS	
	1 × WizPanel
	1 × 2M Length HDMI Cable
	1 × 15M Longth LISB Cable (A-B)

1 × 1.5M Length USB Cable (A-B)

1 × 1.8M Regional Power Cable

1 × Remote Controller

2 × Wzipanel Pens

1 × VESA mount screws (M6)

1 × Wall Mount

2 × Antenna

1 × Quick Install Guide

Accessory Box

ILD-86H

86"

1895.04x1065.9 (88.56")

16:9